



August 1, 2011

To Whom it may concern  
Re "Safe Grip" Non-Slip Floor coating at CommScope Inc., NC

In December 2010 we applied Safe Grip Anti-Skid coating in our Claremont, NC facility.

Safe Grip was applied to the manufacturing facility floor in an area that is used extensively by tow motors, pallet jacks and foot traffic. In this area wooden pallets carrying materials weighing up to 2,000 lbs. are rough positioned on the floor and then pushed across it into processing position. Safe Grip was applied here because oil slung from adjacent processing equipment does settle in the area.

Safe Grip was selected because the traditional non-skid products we have used in the past would not hold up to the severe scraping action seen in this application.

After reviewing the clear and concise Application Instructions provided we participated in a conference call with the Tile Safe staff to discuss the application process and possible issues.

The application process went smoothly. In just a few hours the product was applied and ready to use, the preparation and application was completed after business hours and was ready to bear traffic by the start of our next business day.

To date we have not had a single Safe Grip stripe edge chip, peel or in any fashion become damaged by the pushing of 1 ton wood pallets across it. Thanks to the Tile Safe Team we now have a robust and safe anti-slip working environment for our staff.

Safe Grip Anti-Skid coating has performed as advertised, I am glad to endorse both the company and the product as supplied.

Kevin C. Ewing  
Sr. Process Engineer, Coax  
Phone: (828) 459-5120